



RAPTOR – Air Torque Multiplier

The Most Robust Pneumatic Gear Drive Wrench In The Industry

- HAVS Compliant Design
- Super Quiet Operation <75dBA
- Five Models Available up to 7,800NM (6000ft/lbs)
- Easy Break-Out of Seized Bolts
- Dual operation Trigger
- Ergonomic Pistol Grip
- Optional Double Safety Trigger



Pneumatic Torque Multiplier - RP Series



Integral FRL Unit



Additional Support Handle
(Optional For Larger tools)



Custom Reaction Arms

TECHNICAL DATA

MODEL #	RAPTOR 500	RAPTOR 1000	RAPTOR 2000	RAPTOR 3000	RAPTOR 6000
Square Drive	3/4"	1"	1"	1"	1 1/2"
Min. Torque (Ft/Lbs)	78	148	231	484	714
Max. Torque (Ft/Lbs)	530	1030	2015	3070	6000
Min. Torque (Nm)	106	201	313	656	968
Max. Torque (Nm)	719	1396	2732	4162	8121
Output Accuracy @ Set Torque	+/- 5%	+/- 5%	+/- 5%	+/- 5%	+/- 5%
Repeatability	100%	100%	100%	100%	100%
Duty Cycle	100%	100%	100%	100%	100%
Weight	9lbs/4.1kg	12lbs/5.4kg	16lbs/7.3kg	20lbs/9.1kg	36lbs/16.3kg
RPM @ 10 psi	16.5	7	3.5	1.75	1.25
Tool Max psi	80 psi	70 psi	90 psi	65 psi	90 psi
RPM @ Max psi	44	15	9	4	3

Requires 90psi Compressed Air Supply >30CFM



Extension Attachment